

Standard Bus:
Three Single: 0.25" x 5" Copper Bus
One Single: 0.25" x 4" Copper Bus
1200/1500 Amp at 30/45 degree C rise over 40 degree C Ambient


Alternate Bus:
Three Set: 2 - 0.25" x 5" Copper Bus
One Set: 2 - 0.25" x 4" Copper Bus
2000/2500 Amp at 30/45 degree C rise over 40 degree C Ambient

Standard Paint: "Grey" Munsell #5BG 7.0/0.4

ENCLOSURE OPTIONS:
1) 0.125" #5052H32 Aluminum
2) 12-gauge #304L Stainless Steel

- 11-gauge Steel Enclosure
- Four Screened Louvers
- Kinked Top
- Stainless Steel Hinges
- Provisions for padlock and stainless steel hex (or penta) bolt
- 1" Min. Strike Distance to Ground

Catalog Number
EWM-SBE-0.6-331-CT-44W18D-60H-D95377



Standard Bus:

Three Single: 0.25" x 4W" x 2"D Channel Copper Bus
One Single: 0.25" x 5" Copper Bus
2000/2300 Amp at 30/45 degree C rise over
40 degree C Ambient

Alternate Bus:

Three Set: 2 - 0.25" x 4W x 2D" Channel Copper Bus
One Set: 2 - 0.25" x 4W" x 2"D Channel Copper Bus
3000/3800 Amp at 30/45 degree C rise over
40 degree C Ambient

Standard Paint: "Grey" Munsell #5BG 7.0/0.4

ENCLOSURE OPTIONS:

- 1) 0.125" #5052H32 Aluminum
- 2) 12-gauge #304L Stainless Steel

- 11-gauge Steel Enclosure
- Four Screened Louvers
- Kinked Top
- Stainless Steel Hinges
- Provisions for padlock and stainless steel hex (or penta) bolt
- 1" Min. Strike Distance to Ground

Catalog Number

EWM-SBE-0.6-331-CT-44W18D-60H-D95378